

BB-2600/U

DATA SHEET

Description	Rechargeable, Lithium-Ion, (Carbon/Lithiated Metal Oxide) Battery
National Stock Number	6140-01-467-5853
For Use In	AN/PSC-2 (Digital Communications Terminal)
Rechargeable Replacement for	BA-5600/U
Compatible with	BA-5600/U
Nominal Dimensions	Length: 7.320" (185.98mm) Diameter: 1.550" (39.39mm)
Nominal Weight	.80 Lb (363g)
Maximum Open Circuit Voltage	8.2 V
Nominal Operating Voltage	7.2 V
Capacity per Specification	4.0 Ah
Typical Capacity	5.1 Ah
End of Life Voltage	6.0 V
Discharge Terminals	Nickel Plated Steel Contacts
Charge Terminals	5 ea. Gold Plated Contacts
Operating Temperature Range	-20°C to +60°C (-4°F to +140°F)
Storage Temperature Range	-20°C to +40°C (-4°F to +104°F)
Case Material & Color	Modified ABS plastic, Olive Drab #34088 with Yellow printing
Disposal	Environmentally safe - Contains zero (0)% Mercury or Cadmium Check with local regulations for proper disposal
Charging	Recommended Charger is "Universal 2 HR. Fast Charger" Type PP-8444A/U (NSN: 6130-01-443-0970)
Standard Charge	Charge at constant voltage 8.20 volts dc, for 4 Hrs. (4 Amp. Max.)

WHEN ORDERING SPECIFY P/N:

BT-70443

PACKAGING
UNIT BOX 1 per
MASTER CARTON 36 Ea.
Weight: 34 Lbs. (15.45 Kg)
Cubes: .77Ft ³ (.021 m ³)

